Caviar & Crystal Collection Made with you in mind Proudly made in the UK

CLOUD 9 CAVIAR & CRYSTAL 11MM

- MADE WITH YOU IN MIND
- CLOUD 9 APT
- SUITABLE FOR LUXURY AREAS
- EXCELLENT FOR IMPACT SOUND REDUCTION
- EXCELLENT THERMAL INSULATION PROPERTIES

RECOMMENDED AREAS OF USE

SUITABLE FOR LUXURY USE AREAS DOMESTIC AREAS OF MEDIUM WEAR.

Manufactured in the UK to BS 5808:1991 & BS EN 14499:2015

STANDARD SPECIFICATIONS			
TOP SURFACE	Printed stitch bonded white crepe paper		
BOTTOM SURFACE	Spun bonded non-woven fabricc		
NOMINAL THICKNESS	11.00 mm		
NOMINAL ROLL WEIGHT	19.2 Kg	42.3 lb	
WEIGHT PER UNIT AREA	1912 g/M ²	56 oz/yd²	
ROLL LENGTH	7.33 m	24.0 ft	
ROLL WIDTH	1.37 m	54 in	
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)		
CORE DENSITY	160 Kg/M ³		
PRODUCT DENSITY	173 Kg/M ³		

BS. 5808: 1991 TEST RESULTS - BRITISH STANDARD FOR CARPET UNDERLAYS				
END USE CLASSIFICATION	BS.5808	L/U		
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS.4098	>150 J/m ²		
RETENTION OF WORK OF COMPRESSION	BS.4098	>90 %		
LOSS IN THICKNESS AFTER STATIC LOADING	BS.4939	<5.00 %		
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS.4052	<5.00 %		
RESISTANCE TO CRACKING	BS.5808 (A)	Pass		

INDOOR AIR QUALITY TEST		
TESTED TO ISO16000		
FRENCH VOC EMISSION CLASS LABEL	A+	

OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	2.7 TOG
IMPACT SOUND IMPROVEMENT INDEX		41 dB
(Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		



ISSUE 2 14 NOV - 17

DISCLAIMER

Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Ball & Young has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.

