



CLOUD 9 CONTRACT

- CLOUD 9 CRUMB
- SUITABLE FOR BOTH CONTRACT AND DOMESTIC APPLICATIONS
- EXCELLENT FOR IMPACT SOUND REDUCTION
- EXCELLENT THERMAL INSULATION PROPERTIES

RECOMMENDED AREAS OF USE

HEAVY CONTRACT AND DOMESTIC USE IN AREAS WHERE A FIRM FITTING WITH HIGH ENERGY ABSORPTION IS REQUIRED.

SUITABLE FOR STRETCH-FIT OR DOUBLESTICK APPLICATIONS

Manufactured in the UK to BS EN 14499:2015

STANDARD SPECIFICATIONS		
TOP SURFACE	Silver film with green printing	
BOTTOM SURFACE	Silver film	
NOMINAL THICKNESS	8.00 mm	
NOMINAL ROLL WEIGHT	20.1 kg	44.3 lb
WEIGHT PER UNIT AREA	1334 g/m ²	39 oz/yd ²
ROLL LENGTH	11.0 m	36.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	
CORE DENSITY	160 kg/m ³	
PRODUCT DENSITY	167 kg/m ³	

BS EN 14499 TEST RESULTS - BRITISH STANDARD FOR CARPET UNDERLAYS		
END USE CLASSIFICATION	BS EN 14499	HC/U
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS 4098	>130 J/m ²
RETENTION OF WORK OF COMPRESSION	BS 4098	>90 %
LOSS IN THICKNESS AFTER STATIC LOADING	BS 4939 ISO 3416	<5.00 %
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS ISO 2094 (R05)	<5.00 %
RESISTANCE TO CRACKING	BS EN 14499	Pass

FIRE RESISTANCE TESTS		
EUROPEAN REACTION TO FIRE CLASSIFICATION	EN13501-1	Dfl-S1
HOT METAL NUT TEST	BS 4790	Pass - Low radius of effect

INDOOR AIR QUALITY TEST		
TESTED TO ISO16000		
FRENCH VOC REGULATIONS		A+
FRENCH CMR COMPONENTS		Pass
ITALIAN CAM		Pass
FORMALDEHYDE EMISSION CLASS		E1



OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	2.0 TOG
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		35-37 dB

ISSUE 9 25-JUNE -20