



# ROMA

- HEAVY WEIGHT FLAT SPONGE RUBBER
- SUITABLE FOR HEAVY CONTRACT AND DOMESTIC USE
- RECOMMENDED FOR STAIRS
- CAN BE USED WITH UNDERFLOOR HEATING



## RECOMMENDED AREAS OF USE

AREAS OF HEAVY WEAR INCLUDING STAIRS. SUITABLE WHERE A FIRM FITTING IS REQUIRED.

Manufactured in the UK to BS EN 14499:2015

STANDARD SPECIFICATIONS		
TOP SURFACE	Stitch bonded crepe paper	
BOTTOM SURFACE	Flat sponge rubber	
NOMINAL THICKNESS	6.90 mm	
NOMINAL ROLL WEIGHT	31.0 kg	68.3 lb
WEIGHT PER UNIT AREA	3087 g/m <sup>2</sup>	91 oz/yd <sup>2</sup>
ROLL LENGTH	7.33 m	24.0 ft
ROLL WIDTH	1.37 m	54 in
GUARANTEE	Lifetime of the initial carpet installation (when used in recommended areas)	

BS EN 14499:2015 TEST RESULTS - UK and EU STANDARD for CARPET UNDERLAYS		
END USE CLASSIFICATION	BS EN 14499	HC/U
WORK OF COMPRESSION AFTER 1000 IMPACTS	BS 4098	>90 J/m <sup>2</sup>
RETENTION OF WORK OF COMPRESSION	BS 4098	>75 %
LOSS IN THICKNESS AFTER STATIC LOADING	BS 4939 ISO 3416	<5.00 %
LOSS IN THICKNESS AFTER DYNAMIC LOADING	BS 4052 2094 (R05)	<5.00 %
RESISTANCE TO CRACKING	BS EN 14499	Pass

FIRE RESISTANCE TESTS		
HOT METAL NUT TEST	BS 4790	Pass * Low radius of effect

INDOOR AIR QUALITY TEST		
TESTED TO ISO16000		
EUROFINS INDOOR AIR COMFORT ® STANDARD		Pass
EUROFINS INDOOR AIR COMFORT GOLD ® STANDARD		Pass
FRENCH VOC REGULATIONS		A+
FRENCH CMR COMPONENTS		Pass
ITALIAN CAM		Pass
AgBB/ABG		Pass
FORMALDEHYDE EMISSION CLASS		E1
BREEAM INTERNATIONAL		Compliant
LEED v4 (Outside U.S.)		Compliant
BREEAM ® NOR		Compliant



OTHER RELEVANT TESTS		
THERMAL RESISTANCE (TOG RATING)	BS 4745	0.8 TOG
IMPACT SOUND IMPROVEMENT INDEX (Test/Rated to BS EN ISO 140-8 / BS EN ISO 717-2)		31 dB

ISSUE 6 16-JULY-20